



Hubs

Intelligent control panels









The hub manages all devices within the security system. It notifies users and an alarm response company about any threats instantly. The use of two-way communication allows hubs to send alarm signals, configure devices remotely, and constantly monitor the system's state.

For more information visit the product pages at www.ajax.systems/products

Hub 2	Hub Plus	Hub
2G & Ethernet	Wi-Fi, 3G, 2G & Ethernet	2G & Ethernet
Dual SIM	Dual SIM	1 SIM
100 devices	150 devices	100 devices
25 cameras	50 cameras	10 cameras
50 users	99 users	50 users
9 groups	25 groups	9 groups
up to 16 hours of battery life	up to 16 hours of battery life	up to 15 hours of battery life
Visual alarm verification support	No visual alarm verification support	No visual alarm verification support



Bulletproof Protection

-  Real-time operating system OS Malevich
-  Tampering alarm
-  External power failure alarm or notification
-  Up to 16 hours of operation on the back-up batteries
-  Customizable ping interval: 12–300 s
-  Data encryption
-  Multi-channel communication
-  Resistance to cyber-attacks

Effortless Operation



Instant alarm delivery even with slow Internet connection



Two-way radio communication for testing and configuring of the connected devices



New security and automation features with automatic over the air OS updates



Multiple ways to control the system and connected devices: mobile and desktop apps, key fobs, keypads, smart buttons



Scenarios (reactions and schedules) for security and home automation



Simple Installation

1

Connect devices to the hub with the mobile app

2

Use the SmartBracket to mount the hub without disassembling it

3

Open the app to configure hub's settings

Tech Specs

- Color: white/black
- Installation: indoors
- Radio communication range: up to 2,000 m
- Alarm delivery speed: 0.15 sec
- Alarm notification types: SMS, call, push-notification
- CMS connectivity: SIA, Sur-Gard (Contact ID)
- Power supply: 110–240 V AC (12 V power supply unit is available on demand)
- Battery backup: Li-Ion 2 A·h
Up to 16 hours of operation
- Operating temperature range: from -10°C to +40°C
- Permissible humidity: up to 75%
- Dimensions: 163×163×36 mm
- Weight
Hub/Hub Plus: 350 g
Hub 2: 362 g

Engineering Masterpiece

- Hubs are only 4 cm thick
- No excess modules or buttons
- Built-in backup battery
- Built-in dual path communicators

