



V Series

FD9389-EHTV-V3

5MP Outdoor Dome Camera



Technical Specifications

System Information	
CPU	Multimedia SoC (System-on-Chip)
Flash	4 GB (-L, general available) 8 GB (Limited qty)
RAM	1 GB (-L, general available) 2 GB (Limited qty)

Camera Specifications	
Image Sensor	1/2.8" Progressive CMOS
Max. Resolution	2560x1920 (5MP)
Lens Type	Motorized, Vari-focal, Remote Focus
Focal Length	f = 2.8 ~ 12 mm
Aperture	F1.6 ~ F3.3
Iris Type	P-iris
Field of View	95.4° ~ 28.7° (Horizontal) 68.8° ~ 21.5° (Vertical) 129.6° ~ 35.9° (Diagonal)
Shutter Time	1/5 sec. to 1/32,000 sec.
WDR Technology	WDR Pro
Day/Night	Yes
Removable IR-cut filter	Yes
Illuminators	Built-in IR illuminators, effective up to 40 meters with Smart IR, IR LED*4
Minimum Illumination	0.04 lux @ F1.6 (Color) 0.005 lux @ F1.6 (B/W) 0 lux with IR illumination on
Pan Range	350°

Tilt Range	80°
Rotation Range	350°
Pan/Tilt/Zoom Functionalities	ePTZ: 48x digital zoom (4x on IE plug-in, 12x built in)
Storage	Seamless Recording to MicroSD/SDHC/SDXC card (1TB capacity supported) and recording to network-attached storage (NAS)
Built-in Installation Aids	Remote focus, Pixel calculator, Remote zoom

Video	
Compression	H.265, H.264, MJPEG
Maximum Frame Rate	30 fps @ 2560x1920 (5MP)
Maximum Streams	3 video streams (Up to 8 configurable profiles)
Main Stream	30 fps @ 2560x1920, 2048x1536, 1920x1440, 1600x1200, 1280x960, 800x600, 640x480 (4:3); 30 fps @ 2560x1440, 1920x1080, 1600x904, 1360x768, 1280x720, 640x360 (16:9); 60 fps @ 1920x1080, 1600x904, 1360x768, 1280x720, 640x360 (16:9)
2nd Stream	30 fps @ 1920x1440, 1600x1200, 1280x960, 800x600, 640x480 (4:3); 30 fps @ 1920x1080, 1600x904, 1360x768, 1280x720, 640x360 (16:9); 60 fps @ 1280x720, 640x360 (16:9)
3rd Stream	30 fps @ 1280x960, 800x600, 640x480 (4:3); 30 fps @ 1280x720, 640x360 (16:9); 60 fps @ 1280x720, 640x360 (16:9)
S/N Ratio	55 dB
Dynamic Range	120 dB
Video Streaming	Adjustable resolution, quality and constant bit rate control, Smart Stream III
Image Settings	General settings video title and time stamp overlay, video orientation (flip, mirror, rotation), day/night settings Illuminators illuminators, anti-overexposure, VCA-based Smart IR III Image settings white balance, image adjustment (brightness, contrast, saturation, sharpness, gamma curve), defog, 3DNR, EIS (built-in gyro sensor), scene mode (auto, deblur) Exposure BLC, HLC, exposure control (exposure level, iris adjustment, exposure time, gain control, iris mode), AE speed adjustment, WDR Focus zoom, focus Privacy mask Pixel calculator Scheduled profile settings

Audio	
Audio Capability	Two-way Audio (full duplex)* * Requires AO-015 cable
Compression	G.711, G.726, MPEG-2 AAC-LC
Interface	Built-in microphone External microphone input* External line output* * Requires AO-015 cable.
Effective Range	5 meters

Network	
Users	Live viewing for up to 10 clients
Security	Access list, Password protection, Digest authentication, CSRF protection, HTTPS, IEEE 802.1x, Secure boot, Signed firmware, Trend Micro IoT Security (brute force attack event, cyberattack event), Built-in FIPS 140-2 Level 2 certified Trusted Platform Module (TPM), User access log, User account management
Protocols	802.1X, ARP, Bonjour, CIFS/SMB, DDNS, DHCP, DNS, FTP, HTTP, HTTPS, ICMP, IGMPv3, IPv4, IPv6, NTP, PPPoE, QoS (CoS/DSCP), RTSP/RTP/RTCP, SFTP, SMTP, SNMP, SSL, TCP/IP, TLS 1.2/1.3, UDP, UPnP
Interface	10BASE-T/100BASE-TX Ethernet (RJ-45) *It is highly recommended to use standard CAT5e & CAT6 cables which are compliant with the 3P/ETL standard.
ONVIF	Profile G, S, T, M supported, specification available at www.onvif.org

AI Analytics	
Compute Capability	SoC with built-in hardware deep learning accelerator
Vision Object Analytics	Object Detection: People Vehicle (4-wheeled, 2-wheeled) Human / Vehicle Bestshot Attribute Extraction: People (gender, clothing color, bag, hat) Path Extraction Vehicle (bike, bus, car, motorcycle, truck, color) Human face Bestshot Re-Search Extraction
Applications	Deep Learning VCA (Smart Motion Detection, Smart VCA) Smart VCA - Group 1 Smart Motion Detection (Five-window video motion detection, People detection, Vehicle detection, Time filter), Smart VCA (Intrusion detection, Loitering detection, Line crossing detection, Face detection) Smart VCA - Group 2 Unattended object detection, Missing object detection, Crowd detection
Application available with license	Smart VCA - Group 3 Running detection, Parking Violation Detection, Restricted Zone Detection *Support for more analytic applications and free trial, please visit VIVOTEK website.
RealSight Engine	Smart IR III Deblur WDR White Balance Exposure Control

Solution Integration	
VADP Package	Trend Micro (Default, 3-year free trial)
Video Motion Detection	Motion Detection (Five-window video motion detection)

Alarm and Event	
Event Trigger	Motion detection, Camera tampering detection, Audio detection*, Digital input*, Manual trigger, Periodical trigger, System boot, Recording notification, SD card life expectancy, Shock detection, Cybersecurity events (brute force attack event, cyberattack event) * Requires AO-015 cable
Event Action	Event notification via email, HTTP, FTP/SFTP, NAS server, SD card, digital output*, audio clip*, camera link File upload via email, HTTP, FTP/SFTP, NAS server, SD card *Requires AO-015 cable

General	
Connectors	RJ-45 cable connector for 10/100 Mbps Network/PoE connection Audio line input * Audio line output * Digital input *1 * Digital output *1 (DO+: 12V, 50mA; DO-: 30V, Open Drain, 1A)* * Requires AO-015 cable
LED Indicator	System power and status indicator
Power Input	IEEE 802.3af PoE Class 3
Power Consumption	Max. 12.4W/9.6W (IR on/off)
Dimensions	134 (D) x 116 (H) mm
Weight	990 g
Certifications	EMC CE (EN 55032, EN 55035 Class A), UKCA (BS EN 55032/BS EN 55035 Class A), FCC (FCC Part 15 Subpart B Class A), RCM (AS/NZS CISPR 32 Class A), VCCI (VCCI-CISPR 32 Class A); IC (ICES-003 Issue 7, Class A) Safety UL (UL 62368-1), CB (IEC/EN 62368-1, IEC/EN 62368-1, IEC/EN 62471); UKCA (BS EN IEC 62368-1) Environment NEMA (NEMA 250 Type 4X), IK10 (IEC 62262), IP66 (IEC 60529) IA BIS (IS 13252), BSMI (EMC: CNS 13438, Safety: CNS 14336-1)
Operating Temperature	Starting Temperature: -20°C ~ 50°C (-4°F ~ 122°F) Working Temperature: -35°C ~ 60°C (-31°F ~ 140°F) (IR off) -35°C ~ 50°C (-31°F ~ 122°F) (IR on)
Humidity	98% RH (non-condensing)

System Requirements	
Operating System	Microsoft Windows 10/8/7 Mac 10.12 (Chrome only)
Web Browser	Chrome 58.0 or above
Other Players	VLC: 1.1.11 or above

Included Accessories	
Packing Contents	Quick installation guide, alignment sticker, L-shaped wrench, screw pack

DORI (EN 62676-4 Standard)	
Detection (25PPM/ 8PPF)	Wide: 67.0 m (219.8 ft) Tele: 205.7 m (674.9 ft)
Observation (63PPM/ 19PPF)	Wide: 26.7 m (87.6 ft) Tele: 81.6 m (267.7 ft)
Recognition (125PPM/ 38PPF)	Wide: 13.3 m (43.6 ft) Tele: 41.0 m (134.5 ft)
Identification (250PPM/ 76PPF)	Wide: 6.6 m (21.7 ft) Tele: 20.5 m (67.3 ft)

Ordering Information	
----------------------	--

Part Number	VIO100000750 FD9389-EHTV-V3 (L) -- general available AI dome with 1GB RAM, 4GB eMMC, 5M@30fps, 2.8~12mm motorized lens, VCA and attributes
	VIO100000352 FD9389-EHTV-V3 -- limited qty AI dome with 2GB RAM, 8GB eMMC, 5M@30fps, 2.8~12mm motorized lens, VCA and attributes