



# AP-FXC-0110/0210


## 1-Port/2-Port Indoor FE PoE Extender

### Technical Specifications



Model	AP-FXC-0110	AP-FXC-0210
Compatible Camera List	VIVOTEK Network Cameras	VIVOTEK Network Cameras
<b>Power Specifications</b>		
Extension Distance	2 Units, Daisy-chain Installation Up to 300M Extension (No Local Power Required)	2 Units, Daisy-chain Installation Up to 300M Extension (No Local Power Required)
PoE Input Power	95W/60W/30W PoE	95W/60W/30W PoE
PoE output Power	48~55VDC, Max. 70W	48~55VDC, Max. 70W
PD Power Pin Assignment	1/2 (+), 3/6 (-); 4/5 (+), 7/8 (-)	1/2 (+), 3/6 (-); 4/5 (+), 7/8 (-)
PSE Power Pin Assignment	1/2 (+), 3/6 (-); 4/5 (+), 7/8 (-)	1/2 (+), 3/6 (-); 4/5 (+), 7/8 (-)
PD Fast Ethernet (RJ45)	1	1
PSE Fast Ethernet (RJ45)	1	2
PSE Power On/Off Dip Switch	Supported	Supported
<b>Networking Specifications</b>		
Total Fast Ethernet Port	2	3
Mac Table	2K	2K
Bandwidth	Max. 100 Mbps	Max. 100 Mbps
Switching Capacity	1 Gbps	1 Gbps
Auto-MDI/MDI-X, Auto-Negotiation	Supported	Supported
<b>Mechanical Specifications</b>		
Dimensions	87.72 (L) x 69.4 (W) x 31 (H) mm	108 (L) x 58 (W) x 22 (H) mm
Weight	0.21 kg	0.19 kg
LED Indicators	Power, LAN, PoE	Power, LAN, PoE
<b>Environmental Specifications</b>		
Operating Temperature	0°C ~ 50°C (32°F ~ 122°F)	0°C ~ 50°C (32°F ~ 122°F)
Storage Temperature	-20°C ~ 70°C (-4°F ~ 158°F)	-20°C ~ 70°C (-4°F ~ 158°F)
Operating Humidity	10 ~ 90% (non-condensing)	10 ~ 90% (non-condensing)
<b>Certifications</b>		
EMC	CE, FCC, VCCI, C-Tick	CE, FCC, VCCI, C-Tick
Safety	EN60950-1, IEC60950-1	EN60950-1, IEC60950-1

# Dimensions

AP-FXC-0110



AP-FXC-0210



# Application

